

RECEIVED
CENTRAL FAX CENTER

FEB 29 2008

Appl. No. 10/629,171
Amdt. Dated Feb. 29, 2008
Reply to Office Action of Nov. 29, 2007**AMENDMENTS TO THE SPECIFICATION**

[0015] The extraction tool 1 is made of resilient insulative material. The extraction tool 1 comprises a pull tab 2 and a retention element 3 extending from the pull tab 2. The pull tab 2 has an elongate and strip-like configuration and comprises an engaging portion 21 and a handling portion 22. The engaging portion 21 horizontally extends and defines a circular engaging opening 211 in a substantially central portion thereof. The handling portion 22 extends rearwardly and upwardly from the engaging portion 21. The handling portion 22 defines an elliptic aperture 221 therethrough. The aperture 221 comprises a front portion partially defined through the engaging portion 21. The retention element 3 comprises a connection portion 31 and a fixing portion 32. The connection portion 31 perpendicularly extends from a side edge of the engaging portion 21. The fixing portion 32 extends from the connection portion 31. The fixing portion 32 defines a circular fixing aperture 321. A profile of the fixing aperture 321 is configured corresponding to that of engaging opening 211 of the engaging portion 21. ~~In other embodiment, the handling portion 22 also can extend from the fixing portion 32. Thus, the engaging portion 21 defines a first plate 21, and the fixing portion 32 defines a second plate. A pull tab 22 can not only extend from the first plate 21 but also extend from the second plates 32, and the connection portion 31 linked between the first plate and the second plate.~~